


PVC KABLO KANALLARI
PVC CABLE TRUNKINGS

A Serisi Mini Kanal

A Series Mini Trunking



GENEL ÖZELLİKLER

Ham madde	PVC UL94, V0 M1
Darbe dayanımı	0,5 - 1 Joule
Çalışma sıcaklığı	-25 / +65 C°
Renk	Beyaz RAL 9010
Koruma Sınıfı	IP40
Yangın Dayanımı	960 C°'ye kadar
Tip	2 CTS

EK ÖZELLİKLER

UV dayanımı	UV resistant
Kolay kurulum, boyanabilir, alev yaymaz	Easy install, paintable, self-extinguishing
Ekonomik ve adaptasyonu kolay	Economic and adaptable
Asit ve yağlara karşı dayanımlı	Resistant to acids, oils and greases
Elektrik iletmez	Non-conductive

GENERAL SPECIFICATIONS

Raw material	PVC UL94, V0 M1
Impact resistance	0,5 - 1 Joule
Operating temperature	-25 / +65 C°
Colour	White RAL 9010
IP Ingress Protection	IP40
Fire Resistant	Up to 960 C°
Type	2 Cable Trunking Systems

ADDITIONAL SPECIFICATIONS

UV resistant	UV resistant
Easy install, paintable, self-extinguishing	Easy install, paintable, self-extinguishing
Economic and adaptable	Economic and adaptable
Resistant to acids, oils and greases	Resistant to acids, oils and greases
Non-conductive	Non-conductive

Ölçü Size	Ref. Kodu Code	W (mm)	H (mm)	Ambalaj İçi Miktar Quantity/Pack (m)	Hacim Volume (m ³)	Ağırlık Weight (kg)	Kapasite kg/m Loading Capacity	Alan (mm ²) Loading Area
12 x 12	CT1012012	12	12	378	0,063	21,4	1,5	103,1
15 x 10	CT1015010	15	10	340	0,063	20,4	1,6	107,7
16 x 16	CT1016016	16	16	266	0,083	25,1	2,3	193,9
20 x 10	CT1020010	20	10	240	0,063	20,2	2,3	154,3
20 x 13	CT1020013	20	13	300	0,083	24,3	1,8	210,4
25 x 16	CT1025016	25	16	168	0,083	21,0	2,6	318,3
25 x 25	CT1025025	25	25	130	0,100	20,8	4,0	522,4
30 x 20	CT1030020	30	20	120	0,083	19,8	3,8	803,9
40 x 16	CT1040016	40	16	98	0,083	18,3	4,4	521,4
40 x 25	CT1040025	40	25	80	0,100	17,3	5,6	848,1
40 x 40	CT1040040	40	40	72	0,083	21,0	6,7	1418,1

Standards EN 50085-2-1



Standart üretim 2 m'dir. İstenilen boyda üretim yapılabilir.
Standard length 2 m. Other lengths available.

Naylon ambalajda üretim yapılabilir
Nylon Package available

Kurşun içermeyen çevreye saygılı PVC hammaddeden üretilir.
Lead-Free environment friendly PVC material.