

RG59+2C SPECIFICATION

PRODUCT & SPEC.		RG59+2C		P/I No.		
Conductor	AWG	20AWG				
	Material	CCA				
	Conductor OD	0.81mm±0.01mm				
Diameter of Dielectric	FPE	3.7±0.15mm				
Sheild	Aluminum foil	Golden aluminum thin, 15μ conductive surface facing inward		Cable printing:		
	Braiding	96*0.12±0.01mm CCA		RG59/CCA+2x0.75mm2 Coaxial cable 001M-100M		
Power cable	Material	7*0.37±0.01mm CCA*2core		RG59/CCA+2x0.75mm2 Coaxial cable 001M-300M		
	Insulation	HDPE (Red & Black)				
Jacket	Color	White/ Black		Package:		
	Material	PVC		100m Outer Carton	64*32*23cm (4rolls/ctn)	
	The Average Thickness	0.75mm		300m Outer Carton	36.5*36.5*25.5cm(1roll/ctn)	
	OD	6.2±0.01mm				
	Surface	Smooth				
Basic Characteristics	Coaxial Impedance(ohm)	75±3				
	Conductor allow load current(A)	0.5A				
	Voltage Rating(V)	≤30V				
	Operating Temperature(℃)	-20℃ — +70℃				
	Attenuation [68 ⁰ F(20℃)	Frequency(Mhz)	Attenuation(dB/100m)	INTEGRITY CABLE CO LIMITED Add: Building B,C,H,I, No.30 , The Third Industrial Area, Xiacun, No.102 Matian North Road, Gongming Office, Guangming New District, Shenzhen, China DL:+86-755-29905008 Fax:+86-755-21062682		
		5	2.4			
		55	8.4			
		187	16.1			
		300	20.7			
		450	25.7			
		750	34.4			
		865	37.2			
		1000	40			
		CQ FILE NO.:	CQ-RG59+2C 081CCA			
		CHECKED \$ PROVED				
APPLICATION	CCTV			DRAWING		
CERTIFICATION	CE , ISO9001:2015			DATE		