

DH-HAC-HDW1200R-VF

2MP HDCVI IR Eyeball Camera

HDCVI



System Overview

Experience 1080P full HD video and the simplicity of using existing cabling infrastructure with HDCVI. The Lite series 1080P HDCVI camera features a compact design and offers a high quality image at a friendly price. It offers various vari-focal/fixed lens models with a multi-language OSD and HD/SD switchable output. Its structural flexibility and high cost-performance makes the camera an ideal choice for SMB solutions.

Functions

4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the HCVR, such as sending control signal or triggering alarm. Moreover, HDCVI technology supports PoC for construction flexibility.

* Audio input is available for some models of HDCVI cameras.

Long Distance Transmission

HDCVI technology guarantees real-time transmission at long distance without any loss. It supports up to 800m(1080P)/1200m(720P) transmission via coaxial cable, and up to 300m(1080P)/450m(720P) via UTP cable.*

*Actual results verified by real-scene testing in Dahua's test laboratory.

Simplicity

HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

Smart IR

The camera is designed with IR LED illumination for best lowlight performance. Smart IR is a technology to ensure brightness uniformity in B/W image under low illumination. Dahua's unique Smart IR adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object, and prevents IR LEDs from overexposing images as the object come closer to the camera.

- Max 30fps@1080P
- HD and SD output switchable
- 2.7-13.5mm vari-focal lens
- Max. IR length 30m, Smart IR
- IP67, DC12V



Multi-formats

The camera supports multiple video formats including HDCVI, CVBS and other two common HD analog formats in the market. The four formats can be switched over through OSD menu or by PFM820(UTC controller). This feature makes the camera to be compatible with not only HCVRs but also most end users' existing HD/SD DVRs.

Multi-language OSD

OSD menu provides multiple image adjustments and function settings to meet the requirements of different monitoring scenes. The OSD menu includes configurations such as backlight mode, day/night, white balance, privacy mask and motion detect. The camera supports 11 languages for OSD menu, namely, Chinese, English, French, German, Spanish, Portuguese, Italian, Japanese, Korean, Russian and Polish.

Protection

The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust with IP67 ranking, making it suitable for indoor or outdoor environments.

With working temperature range of -40 °C to +60 °C (-40 °F to +140 °F), the camera is designed for extreme temperature environments.

Supporting ±25% input voltage tolerance, this camera suits even the most unstable power supply conditions. Its 4KV lightning rating provides protection against the camera and its structure from the effects of lightning.


Technical Specification				OSD Menu	Multi-language
Camera				BLC Mode	BLC / HLC / DWDR
Image Sensor	1/2.7" CMOS			WDR	DWDR
Effective Pixels	1920(H)×1080(V), 2MP			Gain Control	AGC
Scanning System	Progressive			Noise Reduction	2D
Electronic Shutter Speed	PAL: 1/25~1/100000s NTSC: 1/30~1/100000s			White Balance	Auto / Manual
Minimum Illumination	0.02Lux/F1.3, 30IRE, 0Lux IR on			Smart IR	Auto / Manual
S/N Ratio	More than 65dB			Certifications	
IR Distance	Up to 30m (98feet)			Certifications	CE (EN55032, EN55024, EN50130-4) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)
IR On/Off Control	Auto / Manual			Interface	
IR LEDs	24			Audio Interface	N/A
Lens				Electrical	
Lens Type	Vari-focal lens / Fixed iris			Power Supply	12V DC ±25%
Mount Type	Board-in			Power Consumption	Max 3.5W (12V DC, IR on)
Focal Length	2.7-13.5mm			Environmental	
Max Aperture	F1.3			Operating Conditions	-40°C ~ +60°C (-40°F ~ +140°F) / Less than 90% RH * Start up should be done at above -40°C (-40°F)
Angle of View	H: 106°~30°			Storage Conditions	-40°C ~ +60°C (-40°F ~ +140°F) / Less than 90% RH
Focus Control	Manual			Ingress Protection & Vandal Resistance	IP67
Close Focus Distance	200mm 7.87"			Construction	
DORI Distance				Casing	Aluminium
Note: The DORI distance is a "general proximity" of distance which makes it easy to pinpoint the right camera for your needs. The DORI distance is calculated based on sensor specification and lab test result according to EN 62676-4 which defines the criteria for Detect, Observe, Recognize and Identify respectively.				Dimensions	Φ119mm×97.4mm (Φ4.69"×3.83")
				Net Weight	0.37kg (0.82lb)
				Gross Weight	0.51kg (1.12lb)
Pan / Tilt / Rotation					
Pan/Tilt/Rotation	Pan: 0° ~ 360° Tilt: 0° ~ 90° Rotation: 0° ~ 360°				
Video					
Resolution	1080P (1920×1080)				
Frame Rate	25/30fps@1080P, 25/30/50/60fps@720P				
Video Output	1-channel BNC high definition video output / CVBS video output (Can switch)				
Day/Night	Auto (ICR) / Manual				

Ordering Information

Type	Part Number	Description
2MP Camera	DH-HAC-HDW1200RP-VF	2MP HDCVI IR Eyeball Camera, PAL
	DH-HAC-HDW1200RN-VF	2MP HDCVI IR Eyeball Camera, NTSC
	PFA13B	Junction box (For use alone)
	PFB204W	Wall mount (For use alone or with PFA152-E pole mount)
	PFA152-E	Pole mount (For use with PFB204W wall mount)
	PFM820	UTC Controller
	PFM800-E	Passive HDCVI Balun
	PFM800-4MP	Passive HDCVI Balun
	PFM801-4MP	Passive HDCVI Balun With Power
	PFM321	12V 1A Power Adapter
	PFM320D-015	12V 1.5A Power Adapter

Accessories

Optional:

PFA13B
Junction boxPFB204W
Wall mountPFA152-E
Pole mountPFM800-E
Passive HDCVI BalunPFM800-4MP
Passive HDCVI BalunPFM801-4MP
Passive HDCVI Balun
With PowerPFM321
12V 1A Power
AdapterPFM320D-015
Power Adapter**Dimensions (mm/inch)**